

Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier	R370A1NL	Revision Date:	01/29/2021
	Product Name:	SP-2888 RG SPRAY BASE	Supercedes Date:	10/12/2020
1.2	Relevant identified uses of the substance or mixture and uses advised against	Component of multicomponent industrial coatings - Industrial use.		
1.3	Details of the supplier of the safety	data sheet		
	Manufacturer :	Specialty Polymer Coatings Division Carboline Company 2150 Schuetz Road St. Louis, Mo. 63146		
		Regulatory / Technical Information: 604-514-9711		
	Datasheet Produced by:	Beebe, Hayli - regulatory@carboline.cor	n	
1.4	Emergency telephone number:	CHEMTREC 1-800-424-9300 (Inside US CHEMTREC +1 703 5273887 (Outside L HEALTH - Pittsburgh Poison Control 1-4	ĴS)	

2. Hazard Identification

2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 2 Carcinogenicity, category 1A Eye Irritation, category 2 Skin Irritation, category 2 Skin Sensitizer, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

Product: R370A1NL

EPOXY RESIN, BIS(GLYCIDYLOXYMETHYL)CYCLOHEXANE, MICROCRYSTALLINE SILICA, NEOPENTYL GLYCOL
DIGLYCIDYL ETHER, BISPHENOL A EPOXY RESIN, EPOXY PHENOL NOVOLAC RESIN, EPOXY DILUENT

HAZARD STATEMENTS

Skin Irritation, category 2 Skin Sensitizer, category 1 Eye Irritation, category 2 Carcinogenicity, category 1A Hazardous to the aquatic environment, Chronic, category 2 PRECAUTION PHRASES	H315 H317 H319 H350-1A H411	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause cancer. Toxic to aquatic life with long lasting effects.
	P201	Obtain special instructions before use.
	P202	Do not handle until all safety precautions have been read and understood.
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P284	Wear respiratory protection.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
	P308+313	IF exposed or concerned: Get medical advice/attention
	P333+313	If skin irritation or rash occurs: Get medical advice/attention.

Collect spillage.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

P391

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

CAS-No.	Chemical Name	<u>%</u>
25068-38-6	BISPHENOL A EPOXY RESIN	25 - <50
9003-36-5	EPOXY RESIN	2.5 - <10
12001-26-2	MICA	2.5 - <10
13463-67-7	TITANIUM DIOXIDE	2.5 - <10
17557-23-2	NEOPENTYL GLYCOL DIGLYCIDYL ETHER	2.5 - <10
14808-60-7	MICROCRYSTALLINE SILICA	2.5 - <10
14228-73-0	BIS(GLYCIDYLOXYMETHYL)CYCLOHEXANE	1.0 - <2.5

28064-14-4 EPOXY PHENOL NOVOLAC RESIN PROPRIETA EPOXY DILUENT RY

1.0 - <2.5 1.0 - <2.5

CAS-No.	GHS Symbols	GHS Hazard Statements	M-Factors
25068-38-6	GHS07-GHS09	H315-317-319-411	0
9003-36-5	GHS07-GHS09	H315-317-411	0
12001-26-2	GHS07	H319-335	0
13463-67-7			0
17557-23-2	GHS07	H315-317	0
14808-60-7	GHS08	H350-372	0
14228-73-0	GHS07-GHS08	H315-317-319-335-373	0
28064-14-4	GHS07-GHS09	H315-317-319-411	0
PROPRIETARY	GHS07	H315-317-319	0
Remarks:	CAS No. 25068-38-6 ide	ntified as CAS No. 1675-54-3, EC No. 216-823	3-5 under REACH Registration

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 **Description of First Aid Measures**

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to eyes and skin. May be harmful if swallowed. Toxic to aquatic organisms.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Vapors may spread long distances and ignite.

FOR SAFETY REASONS NOT TO BE USED: No Information

5.2 Special hazards arising from the substance or mixture No Information

5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Evacuate personnel to safe areas. Use NIOSH approved respiratory protection. Use water spray to cool unopened containers.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours

by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

No Information

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling. **PROTECTION AND HYGIENE MEASURES :** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

STORAGE CONDITIONS: Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(US)

Name	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
BISPHENOL A EPOXY RESIN	25068-38-6	N/E	N/E	N/E
EPOXY RESIN	9003-36-5	N/E	N/E	N/E
MICA	12001-26-2	3 MGM3	N/E	N/E
TITANIUM DIOXIDE	13463-67-7	10 mg/m3	N/E	N/E
NEOPENTYL GLYCOL DIGLYCIDYL ETHEF	17557-23-2	N/E	N/E	N/E
MICROCRYSTALLINE SILICA	14808-60-7	0.025 MGM3	N/E	N/E
BIS(GLYCIDYLOXYMETHYL)CYCLOHEXAN	IE 14228-73-0	N/E	N/E	N/E
EPOXY PHENOL NOVOLAC RESIN	28064-14-4	N/E	N/E	N/E
EPOXY DILUENT	PROPRIETARY	N/E	N/E	N/E
Name	CAS-No.	<u>OSHA PEL</u>	OSHA STEL	
BISPHENOL A EPOXY RESIN	25068-38-6	N/E	N/E	
EPOXY RESIN	9003-36-5	N/E	N/E	

MICA	12001-26-2	20. MPPCF	N/E
TITANIUM DIOXIDE	13463-67-7	15 MGM3	N/E
NEOPENTYL GLYCOL DIGLYCIDYL ETHER	17557-23-2	N/E	N/E
MICROCRYSTALLINE SILICA	14808-60-7	0.05 MGM3	N/E
BIS(GLYCIDYLOXYMETHYL)CYCLOHEXANI	E14228-73-0	N/E	N/E
EPOXY PHENOL NOVOLAC RESIN	28064-14-4	N/E	N/E
EPOXY DILUENT	PROPRIETARY	N/E	N/E

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Use only in an area equipped with explosion proof exhaust ventilation. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1	Information on basic physical and chemical properties Appearance:	Viscous Liquid
	Physical State	Liquid
	Odor	Ероху
	Odor threshold	Not Determined
	рН	Not Determined
	Melting point / freezing point (°C)	Not Determined
	Boiling point/range (°C)	149 F (65 C) - 500 F (260 C)
	Flash Point (°C)	213°F (100°C)
	Evaporation rate	Slower Than Ether
	Flammability (solid, gas)	N/D
	Upper/lower flammability or explosive limits	0.5 - 36.0

	Vapour Pressure, mmHg	Not Determined
	Vapour density	Heavier than Air
	Relative density	N/D
	Solubility in / Miscibility with water	Not Determined
	Partition coefficient: n-octanol/water	N/D
	Auto-ignition temperature (°C)	N/D
	Decomposition temperature (°C)	N/D
	Viscosity	Not Determined
	Explosive properties	N/D
	Oxidising properties	N/D
9.2	Other information	
	VOC Content g/I:	0
	Specific Gravity (g/cm3)	1.55

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

	=	
11.1	Information on toxicological eff	ects
	Acute Toxicity:	
	Oral LD50:	N/D
	Inhalation LC50:	N/D
	Irritation:	Eye Irritation and Skin Irritation, category 2
	Corrosivity:	Unknown
	Sensitization:	Skin Sensitizer, category 1
	Repeated dose toxicity:	Unknown
	Carcinogenicity:	Carcinogenicity, category 1A
	Mutagenicity:	Unknown
	Toxicity for reproduction:	Unknown
	STOT-single exposure:	Unknown
	STOT-repeated exposure:	Unknown
	Aspiration hazard:	Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	<u>Dust/Mist</u> LC50
25068-38-6	BISPHENOL A EPOXY RESIN	11400 mg/kg, rat, oral	23000 mg/kg, dermal, rabbit	>20 mL/kg skin, sensitizer		
9003-36-5	EPOXY RESIN	>5000 mg/kg, oral, rat		Not Available	0.000	0.000
12001-26-2	MICA	Not Available	Not Available	Not Available	0.000	0.000
13463-67-7	TITANIUM DIOXIDE	25000 mg/kg, oral (rat)	Not Available	Not Available	No Information	No Information
17557-23-2	NEOPENTYL GLYCOL DIGLYCIDYL ETHER	4500 mg/kg, oral rat	>2000 mg/kg, dermal, rat	Not Available	0.000	0.000
14808-60-7	MICROCRYSTALLINE SILICA	22500 mg/kg	Not Available	Not Available	0.000	0.000
14228-73-0	BIS(GLYCIDYLOXYMETHYL) CYCLOHEXANE	>2000 mg.kg, oral, rat	>2000 mg/kg, dermal, rat	Not Available	Not Available	Not Available
28064-14-4	EPOXY PHENOL NOVOLAC RESIN	>5000 mg/kg. oral, rat	>2000 mg/kg, rabbit	Not Available	0.000	0.000
PROPRIETA Y	REPOXY DILUENT	Not Available	Not Available	Not Available	0.000	0.000

Additional Information:

This product contains silica which is classified by IARC as a known human carcinogen (Group 1). Crystalline silica is known to cause silicosis. The classification(s) is/are relevant when exposed to these respirable substances in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

12. Ecological Information

12.1 Toxicity:

		•				
	EC	50 48hr (Daphnia):	No info	ormation available.		
	IC5	0 72hr (Algae):	No info	ormation available.		
	LC	50 96hr (fish):	No info	ormation available.		
12.2	Persis	tence and degradability:	No info	ormation available.		
12.3	Bioace	cumulative potential:	No info	ormation available.		
12.4	Mobili	ty in soil:	No info	ormation available.		
12.5		ts of PBT and vPvB sment:	The pr	oduct does not meet t	he criteria for PBT/VPvB	in accordance with Annex XIII.
12.6	Other	adverse effects:	No info	ormation available.		
<u>CAS-</u>	<u>No.</u>	Chemical Name		<u>EC50 48hr</u>	<u>IC50 72hr</u>	LC50 96hr
	No. 8-38-6	<u>Chemical Name</u> BISPHENOL A EPOXY RESIN		<u>EC50 48hr</u> 2.1 mg/l (daphnia)	<u>IC50 72hr</u> 11 mg/l (algae)	<u>LC50 96hr</u> 1.3 mg/l (fish)
	8-38-6					
25068 9003-	8-38-6	BISPHENOL A EPOXY RESIN		2.1 mg/l (daphnia) 1.6 mg/l (Daphnia	11 mg/l (algae)	1.3 mg/l (fish)
25068 9003- 1200 ⁻	8-38-6 -36-5	BISPHENOL A EPOXY RESIN EPOXY RESIN		2.1 mg/l (daphnia) 1.6 mg/l (Daphnia Magna)	11 mg/l (algae) 1.8 mg/l (Green Algae)	1.3 mg/l (fish) 0.55 mg/l (Rainbow Trout)
25068 9003- 1200 13463	8-38-6 -36-5 1-26-2	BISPHENOL A EPOXY RESIN EPOXY RESIN MICA	THER	2.1 mg/l (daphnia) 1.6 mg/l (Daphnia Magna) No information	11 mg/l (algae) 1.8 mg/l (Green Algae) No information	1.3 mg/l (fish) 0.55 mg/l (Rainbow Trout) No information
25068 9003- 1200 13463 1755	8-38-6 -36-5 1-26-2 3-67-7	BISPHENOL A EPOXY RESIN EPOXY RESIN MICA TITANIUM DIOXIDE	ETHER	2.1 mg/l (daphnia) 1.6 mg/l (Daphnia Magna) No information No information	11 mg/l (algae) 1.8 mg/l (Green Algae) No information No information	1.3 mg/l (fish) 0.55 mg/l (Rainbow Trout) No information No information
25068 9003- 1200 13463 1755 14808	8-38-6 -36-5 1-26-2 3-67-7 7-23-2	BISPHENOL A EPOXY RESIN EPOXY RESIN MICA TITANIUM DIOXIDE NEOPENTYL GLYCOL DIGLYCIDYL E	THER	2.1 mg/l (daphnia) 1.6 mg/l (Daphnia Magna) No information No information No information	11 mg/l (algae) 1.8 mg/l (Green Algae) No information No information No information	1.3 mg/l (fish) 0.55 mg/l (Rainbow Trout) No information No information No information
25068 9003 1200 13463 1755 14808 14228 28064	8-38-6 -36-5 1-26-2 3-67-7 7-23-2 8-60-7 8-73-0 4-14-4	BISPHENOL A EPOXY RESIN EPOXY RESIN MICA TITANIUM DIOXIDE NEOPENTYL GLYCOL DIGLYCIDYL E MICROCRYSTALLINE SILICA BIS(GLYCIDYLOXYMETHYL)	ETHER	2.1 mg/l (daphnia) 1.6 mg/l (Daphnia Magna) No information No information No information No information	11 mg/l (algae) 1.8 mg/l (Green Algae) No information No information No information No information	1.3 mg/l (fish) 0.55 mg/l (Rainbow Trout) No information No information No information No information

13. Disposal Considerations

WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, 13.1 dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

	•	
14.1	UN number	UN3082
14.2	UN proper shipping name	Environmentally Hazardous Substance, Liquid N.O.S.
	Technical name	(Epoxy Resin)
14.3	Transport hazard class(es)	9
	Subsidiary shipping hazard	N/A
14.4	Packing group	III
14.5	Environmental hazards	Marine pollutant: Yes (Epoxy Resin)
14.6	Special precautions for user	No information available.
	EmS-No.:	F-A, S-F
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	No information available.

15. Regulatory Information

^{15.1} Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Carcinogenicity, Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation **Sara Section 313**:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name

No Sara 313 components exist in this product.

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

CAS-No.

<u>%</u>

No TSCA 12(b) components exist in this product.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	<u>CAS-No.</u>
FELDSPAR	68476-25-5
Pennsylvania Right-To-Know	

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name FELDSPAR CAS-No. 68476-25-5

CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory (DSL)

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.