



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** Dry Graphite Lube - 10 oz

**Other means of identification**  
**Product Code** No. 03094 (Item# 1003362)

**Recommended use** Dry film lubricant

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufactured or sold by:**

**Company name** CRC Industries, Inc.  
**Address** 885 Louis Dr.  
Warminster, PA 18974 US

**Telephone**

**General Information** 215-674-4300  
**Technical Assistance** 800-521-3168  
**Customer Service** 800-272-4620  
**24-Hour Emergency (CHEMTREC)** 800-424-9300 (US)  
**Website** www.crcindustries.com

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1  
Gases under pressure Liquefied gas

**Health hazards** Skin corrosion/irritation Category 2  
Serious eye damage/eye irritation Category 2A  
Specific target organ toxicity, single exposure Category 3 respiratory tract irritation  
Specific target organ toxicity, single exposure Category 3 narcotic effects  
Specific target organ toxicity, repeated exposure Category 2  
Aspiration hazard Category 1

**Environmental hazards** Hazardous to the aquatic environment, acute hazard Category 2  
Hazardous to the aquatic environment, long-term hazard Category 2

**OSHA defined hazards** Not classified.

### Label elements



**Signal word**

Danger

**Hazard statement**

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

## Precautionary statement

### Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Do not breathe mist/vapors. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Wear eye protection/face protection. Wear protective gloves.

### Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

### Storage

Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Hazard(s) not otherwise classified (HNOC)

None known.

### Supplemental information

None.

---

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
naphtha (petroleum), hydrotreated light		64742-49-0	25 - 50
isopropyl alcohol		67-63-0	10 - 25
n-butane		106-97-8	10 - 25
propane		74-98-6	10 - 25
graphite		7782-42-5	≤ 3
methylcyclohexane		108-87-2	≤ 3
solvent naphtha (petroleum), light aliph.		64742-89-8	≤ 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

---

## 4. First-aid measures

### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

### Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

### Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

### Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

### General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

---

## 5. Fire-fighting measures

### Suitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

### Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire-fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not breathe mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.
<b>Conditions for safe storage, including any incompatibilities</b>	Level 3 Aerosol.  Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
graphite (CAS 7782-42-5)	PEL	5 mg/m <sup>3</sup>	Respirable fraction.
		15 mg/m <sup>3</sup>	Total dust.
isopropyl alcohol (CAS 67-63-0)	PEL	980 mg/m <sup>3</sup>	
		400 ppm	
methylcyclohexane (CAS 108-87-2)	PEL	2000 mg/m <sup>3</sup>	
		500 ppm	

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	PEL	400 mg/m3	
		100 ppm	
propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	PEL	400 mg/m3	
		100 ppm	

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

Components	Type	Value	Form
graphite (CAS 7782-42-5)	TWA	15 mppcf	

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction.
isopropyl alcohol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
methylcyclohexane (CAS 108-87-2)	TWA	400 ppm	
	STEL	1000 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
graphite (CAS 7782-42-5)	TWA	2.5 mg/m3	Respirable.
isopropyl alcohol (CAS 67-63-0)	STEL	1225 mg/m3	
		500 ppm	
	TWA	980 mg/m3	
methylcyclohexane (CAS 108-87-2)	TWA	400 ppm	
		1600 mg/m3	
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	400 ppm	
		400 mg/m3	
n-butane (CAS 106-97-8)	TWA	100 ppm	
		1900 mg/m3	
propane (CAS 74-98-6)	TWA	800 ppm	
		1800 mg/m3	
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TWA	1000 ppm	
		400 mg/m3	
		100 ppm	

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
isopropyl alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

\* - For sampling details, please see the source document.

<b>Appropriate engineering controls</b>	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.
<b>Individual protection measures, such as personal protective equipment</b>	
<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles).
<b>Skin protection</b>	
<b>Hand protection</b>	Wear protective gloves such as: Neoprene. Nitrile.
<b>Other</b>	Wear appropriate chemical resistant clothing.
<b>Respiratory protection</b>	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

---

## 9. Physical and chemical properties

### Appearance

<b>Physical state</b>	Liquid.
<b>Form</b>	Aerosol.
<b>Color</b>	Black.
<b>Odor</b>	Solvent.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	Not available.
<b>Flash point</b>	-20.2 °F (-29.0 °C) Pensky-Martens Closed Cup
<b>Evaporation rate</b>	Moderate.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	0.9 %
<b>Flammability limit - upper (%)</b>	12.7 %
<b>Vapor pressure</b>	101.3 kPa
<b>Vapor density</b>	1.55 (air = 1)
<b>Relative density</b>	0.66
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	482 °F (250 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	< 20.5 mm <sup>2</sup> /s (104 °F (40 °C))
<b>Percent volatile</b>	Not available.

---

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.

<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Heat, flames and sparks. Contact with incompatible materials.
<b>Incompatible materials</b>	Acids. Strong oxidizing agents. Chlorine. Fluorine. Isocyanates. Nitrates.
<b>Hazardous decomposition products</b>	Carbon oxides.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause drowsiness or dizziness. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**Symptoms related to the physical, chemical and toxicological characteristics**      Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

### Information on toxicological effects

**Acute toxicity**      May be fatal if swallowed and enters airways.

Components	Species	Test Results
isopropyl alcohol (CAS 67-63-0)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	5030 - 7900 mg/kg
<b>Inhalation</b>		
LC50	Rat	16000 ppm, 4 hours
<b>Oral</b>		
LD50	Rat	4700 - 5800 mg/kg

**Skin corrosion/irritation**      Causes skin irritation.

**Serious eye damage/eye irritation**      Causes serious eye irritation.

### Respiratory or skin sensitization

<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**      No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity**      Not classifiable as to carcinogenicity to humans.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

#### US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**      This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity - single exposure**      May cause respiratory irritation. May cause drowsiness or dizziness.

**Specific target organ toxicity - repeated exposure**      May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard**      May be fatal if swallowed and enters airways.

**Chronic effects**      Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure.

---

## 12. Ecological information

<b>Ecotoxicity</b>	Toxic to aquatic life with long lasting effects.
<b>Persistence and degradability</b>	No data is available on the degradability of any ingredients in the mixture.
<b>Bioaccumulative potential</b>	
<b>Partition coefficient n-octanol / water (log Kow)</b>	
isopropyl alcohol	0.05
methylcyclohexane	3.61
n-butane	2.89
propane	2.36
<b>Bioconcentration factor (BCF)</b>	
naphtha (petroleum), hydrotreated light	10 - 25000
<b>Mobility in soil</b>	No data available.
<b>Other adverse effects</b>	The product contains volatile organic compounds which have a photochemical ozone creation potential.

---

## 13. Disposal considerations

<b>Disposal instructions</b>	If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	D001: Waste Flammable material with a flash point <140 F
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

## 14. Transport information

### DOT

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	N82
<b>Packaging exceptions</b>	306
<b>Packaging non bulk</b>	None
<b>Packaging bulk</b>	None

### IATA


<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not applicable.
<b>ERG Code</b>	10L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.

### IMDG


<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS, Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-

**Packing group** Not applicable.  
**Environmental hazards**  
**Marine pollutant** Yes, but exempt from the regulations.  
**EmS** F-D, S-U  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

DOT; IMDG



IATA



---

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Not listed.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

**CERCLA Hazardous Substances: Reportable quantity**

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

n-butane (CAS 106-97-8)

propane (CAS 74-98-6)

**Safe Drinking Water Act (SDWA)** Not regulated.

**FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**

isopropyl alcohol (CAS 67-63-0)

Low priority

**Food and Drug Administration (FDA)** Not regulated.



## Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Classified hazard categories** Flammable (gases, aerosols, liquids, or solids)  
Gas under pressure  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard

### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312 Hazardous chemical** Yes

**SARA 313 (TRI reporting)**  
Not regulated.

## US state regulations

### US. New Jersey Worker and Community Right-to-Know Act

graphite (CAS 7782-42-5)  
isopropyl alcohol (CAS 67-63-0)  
methylcyclohexane (CAS 108-87-2)  
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
n-butane (CAS 106-97-8)  
propane (CAS 74-98-6)  
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

### US. Massachusetts RTK - Substance List

graphite (CAS 7782-42-5)  
isopropyl alcohol (CAS 67-63-0)  
methylcyclohexane (CAS 108-87-2)  
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
n-butane (CAS 106-97-8)  
propane (CAS 74-98-6)  
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

### US. Pennsylvania Worker and Community Right-to-Know Law

graphite (CAS 7782-42-5)  
isopropyl alcohol (CAS 67-63-0)  
methylcyclohexane (CAS 108-87-2)  
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
n-butane (CAS 106-97-8)  
propane (CAS 74-98-6)  
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

### US. Rhode Island RTK

graphite (CAS 7782-42-5)  
isopropyl alcohol (CAS 67-63-0)  
methylcyclohexane (CAS 108-87-2)  
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
n-butane (CAS 106-97-8)  
propane (CAS 74-98-6)  
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

### California Proposition 65



**WARNING:** Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### California Proposition 65 - CRT: Listed date/Developmental toxin

toluene (CAS 108-88-3) Listed: January 1, 1991

### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

isopropyl alcohol (CAS 67-63-0)  
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
n-butane (CAS 106-97-8)  
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

## Volatile organic compounds (VOC) regulations

### EPA

**VOC content (40 CFR 51.100(s))** > 97 %

**Consumer products (40 CFR 59, Subpt. C)** Not regulated

### State

**Consumer products** Not regulated

**VOC content (CA)** > 97 %

**VOC content (OTC)** > 97 %

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

---

## 16. Other information, including date of preparation or last revision

**Issue date** 10-28-2020

**Prepared by** Allison Yoon

**Version #** 01

**Disclaimer** The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..

**Revision information** This document has undergone significant changes and should be reviewed in its entirety.