

MATERIAL SAFETY DATA SHEET

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements

U.S. DEPARTMENT OF LABOR

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As Used on Label and List) INNERCOAT	<i>Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.</i>
----------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------

Section I

Manufacturer's Name The Trenton Corporation	Emergency Telephone Number 734- 424-3600
-------------------------------------------------------	----------------------------------------------------

Address (Number, Street, City, State, and ZIP Code) 7700 Jackson Road	Telephone Number for Information 734- 424-3600
---------------------------------------------------------------------------------	----------------------------------------------------------

Ann Arbor, Michigan 48103	Date Prepared January 17, 2008
----------------------------------	------------------------------------------

	Signature of Preparer (optional)
--	----------------------------------

Section II - Hazardous Ingredients/Identify Information

Hazardous Components (Specific Chemical Identity; Common Name(s)) OSHA PEL; ACGIH TLV; Other Limits Recommended; % (optional)

No component is present at sufficient concentration to require a hazardous classification.

Section III - Physical/Chemical

Boiling Point Over 500°F	Specific Gravity (H ₂ O = 1) Less than 1 (.9)
Vapor Pressure (mm Hg.) Not Determined	Melting Point 160°F - 175°F
Vapor Density (AIR = 1) Not Determined	Evaporation Rate (Butyl Acetate = 1) Non-Volatile
Solubility in Water Negligible	

Appearance and Odor

Brown with a bland wax odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) Open Cup - 500°F minimum	Flammable Limits in Air Estimated	LEL 0.9% Vol.	UEL 7.0% Vol.
--------------------------------------------------------------	---------------------------------------------	-------------------------	-------------------------

Extinguishing Media

CO₂, Dry Chemical, or Foam.

Special Fire Fighting Procedures

Treat the same as an oil fire.

Unusual Fire and Explosion Hazards

None

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	

Incompatibility (*Materials to Avoid*)

Avoid strong oxidants

Hazardous Decomposition or Byproducts

Burning will release CO, CO₂ and other hydrocarbon byproducts.

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? Possible (fume)	Skin? Possible	Ingestion? Unlikely
--------------------	---------------------------------------	--------------------------	-------------------------------

Health Hazards (*Acute and Chronic*)

No known health hazards

Carcinogenicity:	NTP? Not Listed	IARC Monographs? Not Listed	OSHA Regulated? Not Regulated
------------------	---------------------------	---------------------------------------	-----------------------------------------

Signs and Symptoms of Exposure

None known

Medical Conditions Generally Aggravated by Exposure **None Known**

Emergency and First Aid Procedures **FIRST AID: INHALATION: If overcome by fumes, move to fresh air. SKIN: If hot, treat as a thermal burn. EYES: Flush with water. INGESTION: Do not induce vomiting except to prevent asphyxiation.**

Section VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled

Confine spill with dirt or sand. Allow to solidify. Then scrape up and sweep up.

Waste Disposal Method

Burn in approved hydrocarbon incinerator or bury in approved landfill.

Precautions to be Taken in Handling and Storing

Avoid splattering hot wax on skin. Store away from heat and oxidants.

Other Precautions

ACGIH recommends exposure limit of 2 mg/m³ for wax fumes.

Section VIII - Control Measures

Respiratory Protection (*Specify Type*)

None required unless in confined and enclosed area.

Ventilation	Local Exhaust Not Required	Special Not Required
	Mechanical (<i>General</i>) Should be Adequate	Other Not Required

Protective Gloves

Oil & heat resistant gloves recommended.

Eye Protection

Goggles recommended.

Other Protective Clothing or Equipment - Clothing **that covers bare skin is recommended.**

Work/Hygienic Practices - **General hygiene practices are adequate.**

* The information herein is given in good faith. However, no warranty, expressed or implied, is made regarding this data.