# MATERIAL SAFETY DATA SHEET

WHMIS HAZARD: D2A, D2B

## **SECTION 1 – PRODUCT IDENTIFICATION AND USE**

Product Identifier..... SP-2831 BRUSH GRADE BASE

Product Code...... **850-438** 

Product Use ..... Exterior coating for pipelines.

Manufacturer's Name...... SPECIALTY POLYMER COATINGS, INC.

Supplier's Name...... SPECIALTY POLYMER COATINGS USA, INC.

24 HR. TELEPHONE NUMBER ..... CHEMTREC: 1-800-424-9300

INFORMATION NUMBER ..... 1-281-595-3530

## **SECTION 2 – HAZARDOUS INGREDIENTS**

<b>Hazardous Ingredients</b>	<u>%</u>	C.A.S. #	Lethal Dose 50%	Lethal Conc. 50%	TLV
			Species & route	Species & route	TWA-ACGIH
Epoxy Resin	15-40	25068-38-6	3000 mg/kg Rat Oral	N/AV	N/AV
Titanium Dioxide	3-7	13464-67-7	N/AV	N/AV	10 mg/M3
Potassium Alumino Silicate	3-7	12001-26-2	N/AV	N/AV	3 mg/M3
Modified Triglycidyl Ether	5-10	30499-70-8	N/AV	N/AV	N/AV
Sorbitol Polyglycidyl Ether	3-7	68412-01-1	N/AV	N/AV	N/AV
Acrylate Ester of 1,6 Hexanediol	0.1-1.0	13048-33-4	5000 mg/kg Rat Oral	N/AV	N/AV
Wollastonite	15-40	13983-17-0	N/AV	N/AV	10 mg/M3
Siloxanes and Silicones, Reaction	0.5-1.5	67762-90-7	N/AV	N/AV	10 mg/M3
Products with Silica					

CEPA STATUS: All of the ingredients of this product are on the DSL.

TSCA STATUS: All of the ingredients of this product are on the TSCA Inventory.

#### **SECTION 3 – PHYSICAL DATA**

Physical State ..... Liquid.

Odour and Appearance...... Grey, viscous liquid.

Odour Threshold (ppm)...... N/AV

Vapour Density (air=1) ...... N/AV

Evaporation Rate (butyl acetate=1)..... N/AV

Freezing Point ...... N/AP

pH......N/AV

Specific Gravity (water=1)..... 1.6

Coefficient of water/oil distribution..... N/AV

Solubility in water (20°C / 68°F) ....... Negligible.

#### **SECTION 4 – FIRE AND EXPLOSION**

Flammability ...... Does not burn readily.

Flammability: If Yes, under which conditions?.... Excessive heat, sparks and open flame. In contact with

incompatible substances. Surrounding fire.

Special Procedures .......... Firefighters should wear the usual protective gear.

Use Self- Contained Breathing Apparatus.

Flash Point and Method .... >93.3°C (>199.94°F) PMCC.

Upper Flammability Limit (% by volume).... N/AV

Lower Flammability Limit (% by volume) ... N/AV

Autoignition Temperature ...... N/AV

Hazardous Combustion Product....... Oxides of Carbon (CO, CO2), Oxides of Nitrogen,

Aldehydes, acids.

**Explosion Data:** 

Sensitivity to Static Discharge ...... N/AP

#### **SECTION 5 – REACTIVITY DATA**

Chemical Stability..... Yes. Product is stable in non-emergency conditions.

Chemical Stability..... No. Avoid heat, flames, sparks, ignition sources, strong acids or bases in bulk.

Incompatibility with other substances.... Yes. Oxidizing agents. Acids, Bases, amines.

Reactivity and under what conditions .... Elevated temperatures.

Hazardous Decomposition Products ..... Oxides of Carbon, Oxides of Nitrogen, Aldehydes, and acids.

## **SECTION 6 – TOXICOLOGICAL PROPERTIES**

Route of Entry ...... Skin, eyes, inhalation, ingestion

Effects of Acute Exposure:

Skin Contact...... May cause skin burns. May cause allergic skin reactions.

Skin Absorption ...... Can be absorbed through the skin.

Eye Contact ...... Causes eye irritation

Ingestion...... Harmful if swallowed.

Effects of Chronic Exposure to Product..... May cause lung damage, skin sensitization, dermatitis,

respiratory sensitization.

Exposure Limits ...... Refer to Section 2 – Hazardous Ingredients.

Irritancy of Product ....... Refer to Effects of Chronic Exposure to Product.

Carcinogenicity ...... N/AV

Teratogenicity...... Not reported.

Reproductive Toxicity.... N/AV

Mutagenicity..... N/AV

Synergistic Products...... N/AV

#### **SECTION 7 – PREVENTATIVE MEASURES**

Persona	l Protective	Equi	pment:
---------	--------------	------	--------

Gloves ........ Chemical resistant gloves with a long cuff with a long cuff that will overlap the clothing sleeves should be worn when handling this product. The glove / clothing overlaps should be sealed by tape. Check with the glove manufacturer to determine the proper glove type.

Respirator .... Wear an appropriate, properly fitted vapour respirator (NIOSH / OSHA approved) during application where vapour / mist are likely to be encountered, e.g. confined spaces and during winter construction or when the substrate is preheated. For outdoor application and areas with adequate ventilation, the use of a respirator is normally not required. Follow the respirator manufacturer's recommendations. A dust respirator should be worn for any activity such as sanding or grinding of cured coating.

Eyes ............ Wear splash proof chemical safety goggles and / or face shield.

Footwear..... Wear impervious boots.

Clothing...... Long-sleeved clothing is to be worn over regular clothing to cover all exposed areas of arms, legs or torso during mixing and application of the coating. Breathable clothing, such as cotton or disposable coveralls, is recommended.

Other...... Emergency eyewash and a shower should be in close proximity, where possible. A barrier cream may be used, in conjunction with the stated protective measures, as an additional safeguard against skin contact.

Engineering Controls ... Mechanical ventilation, both dilution and exhaust may be utilized to keep exposure below the TLV. Extra ventilation should be provided in enclosed spaces.

Leak and Spill Procedure ..... Remove all sources of ignition. Wear appropriate safety equipment as listed above. Soak up spills with inert absorbent materials and place in closed containers. Prevent run-off from reaching storm or sewer drains.

Waste Disposal..... Dispose of according to Federal, Provincial, and Municipal regulations in Canada and Federal, State, and County regulations in the United States of America.

Handling Procedures and Equipment..... All equipment must be grounded. Keep container closed when not in use. Wear appropriate personal protective equipment. Maintain good personal hygiene, wash thoroughly after using, particularly before eating or going on breaks.

Storage Requirements ..... Store in a cool, dry, well-ventilated area away from incompatible materials and all sources of ignition. Keep in a tightly sealed container.

#### **SECTION 8 – SHIPPING INFORMATION**

PIN/Class/Pkg.Grp. ..... N/AP

Proper Shipping Name ..... NOT REGULATED

#### **SECTION 9 – FIRST AID MEASURES**

Specific Measures:

artificial respiration. Get Medical attention.

Ingestion...... Get Medical attention **IMMEDIATELY**.

Eye Contact ........... Flush with water for at least 15 minutes, hold eyelids apart to ensure complete

irrigation of all eye and lid tissue, and get Medical attention.

Skin Contact.......... Wash with water and mild soap for at least 15 minutes. Remove contaminated

clothing and wash before re-use. Get Medical attention.

## CAUTION---NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

#### **SECTION 10 – PREPARATION DATE OF MSDS**

Prepared by...... Technical Department of Specialty Polymer Coatings, Inc. with information provided

by suppliers of raw materials used in the manufacture of SP-2831 Brush Grade Base.

Phone Number...... (604) 514-9711

Preparation Date..... December 13, 2007

Revision Date...... December 21, 2009

**NOTE:** While Specialty Polymer Coatings, Inc. believes that the data contained herein are accurate and derived from qualified sources, the data are not to be taken as a warranty or representation for which Specialty Polymer Coatings, Inc. assumes legal responsibility. The data is offered solely for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, Provincial / State, and Municipal / County laws and regulations.

# ABBREVIATIONS USED IN PREPARING THIS MSDS

% - Percent	# - Number	< - Less Than	> - Greater Than	@ - At		
ACGIH		American Conference	of Governmental Industrial l	Hygienists		
C						
C.A.S. #		Chemical Abstract Nur	mber			
CEIL		Ceiling Limit				
CEPA		Canadian Environmental Protection Agency				
CFR						
DOT		Department of Transportation				
		Domestic Substance List				
		Dermal Lethal Dose - 50% Death				
F						
FP						
		Grams/kilogram				
		Hazardous Material Information System				
		International Agency for Research on Cancer				
		International Air Trans				
		International Marine D				
		Inhalation Lethal Conc	centration - 50% Death			
Kg						
		Pounds per Gallon				
		Lower Explosion Limi				
		Lethal Concentration (				
		Lethal Dosage (50% D	eatn)			
-		Milliarems per Litra				
		Milligrams per Litre Milligrams per Meter (	Cubad			
		Millimeters of Mercury				
N/AP		· · · · · · · · · · · · · · · · · · ·	y			
N/AV		**				
N/D						
NFPA HAZARD I			2 - Moderate, 1 - Slight, 0 -	None X - Blank		
NIOSH			ccupational Safety & Health			
NTP						
Oral-LD50		0.	2			
			nd Health Administration			
		Permissible Exposure				
		Product Identification				
		Packing Group				
		Pensky-Martens Close	d Cup			
ppm						
SARA		=	ts & Reauthorization Act (19	986)		
SETA		=				
STEL		Short Term Exposure l	Limit			
TDG		Transportation of Dang	gerous Goods Act and Pursu	ant Regulations		
TLV		Threshold Limit Value				
TWA		Time Weighted Averag				
TSCA		Toxic Substances Con				
WHMIS		Workplace Hazardous	Material Information System	n		