

SECTION 1 – PRODUCT IDENTIFICATION AND USE				
Material Denso Protal 7125 “A”		TDG Classification Resin Solution, UN 1866, Class 3, PG III		
Manufacturer's Name Denso North America Inc.		Supplier's Name Denso North America Inc.		
Street Address 90 Ironside Crescent, Unit 12		Street Address 90 Ironside Crescent, Unit 12		
City Toronto	Province/Country Ontario	City Toronto	Province/Country Ontario	
Postal Code M1X 1M3	Emergency Telephone No. (613) 996-6666	Postal Code M1X 1M3	Emergency Telephone # (613) 996-6666	
Product Class Vinyl Ester	Chemical Family Not Available	Manufacturer's Code 2070-2031		
WHMIS Classification Class B, Division 2 Class D, Division 2, Sub.A	Trade Name & Synonyms Denso Protal 7125 “A”	Material Use On-site Liquid Coating for Metal Pipes		
SECTION 2 – HAZARDOUS INGREDIENTS				
Ingredients	%	CAS Number	LD50 of Material (Specific Species & Route)	LC50 of Material (Specific Species)
Nepheline Syenite	40-70	37244-96-5	N/A=Not Available	N/A = Not Available
Vinyl Ester Resin	15-40	36425-16-8	Oral> 4000mg/kg Rat	N/A
Styrene Monomer,Inhibited	10-30	100-42-5	Oral> 5000mg/kg Rat	4hrs 2770ppm Rat
Titanium Dioxide	3-7	13463-67-7	N/A	N/A
Organophillic Clay	3-7	71011-26-2	N/A	N/A
Trimethylolpropane Trimet	1-5	3290-92-4	N/A	N/A
Propylene Carbonate	0.5-1.5	108-32-7	Oral> 29000mg/kg Rat	N/A
N,N-Diethylaniline	0.1-1.0	91-66-7	Oral> 920mg/kg Rat	4hrs 4000ppm Rat
SECTION 3 – PHYSICAL DATA				
Physical State Gas <input type="checkbox"/> Liquid <input checked="" type="checkbox"/> Solid <input type="checkbox"/>		Odour and Appearance Irritating Odour, White Liquid		Odour Threshold (PPM) Not Available
Vapour Pressure (mm Hg) 7.0	Vapour Density (air = 1) 4.0	Evaporation Rate Not Available	Boiling Point (° C) 146°C	Freezing Point (° C) Not Available
% Volatile (by volume) 1.85	Solubility in Water (20° C) Insoluble	pH Not Available	Specific Gravity 1.56	Coeff Water/Oil Dist Not Available
SECTION 4 – FIRE AND EXPLOSION DATA				
Flammability Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>		If Yes, Under What Conditions? Flammable Liquid		
Means of Extinction Water Spray, Water Fog, Dry Chemical, Foam				
Special Procedures				
Flashpoint (° C) and Method 27°C (Setaflash Closed Cup)	Upper Explosion Limit (% by volume) 7.0	Lower Explosion Limit (% by volume) 1.0		
Auto Ignition Temperature (° C) Not Available	TDG Flammability Classification Flammable Liquid Class 3	Hazardous Combustion Products CO, CO2, Phenolics		
Sensitivity to Mechanical Impact No	Rate of Burning Not Applicable	Explosive Power Not Applicable	Sensitivity to Static Discharge Yes	

SECTION 5 – REACTIVITY DATA			
Chemical Stability Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>		If No, Under What Conditions? Avoid Excessive Heating Over Long Periods of Time	
Hazardous Polymerization Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>		May Occur	
Reactivity, and Under What Conditions?		Heat, Open Flames, Sparks, Aging	
Hazardous Decomposition Products		Not Available	
SECTION 6 – TOXICOLOGICAL PROPERTIES			
Route of Entry Skin Contact <input checked="" type="checkbox"/> Skin Absorption <input checked="" type="checkbox"/> Eye Contact <input checked="" type="checkbox"/> Inhalation Acute <input checked="" type="checkbox"/> Inhalation Chronic <input type="checkbox"/> Ingestion <input checked="" type="checkbox"/>			
Effects of Acute Exposure to Material Contact with Eyes will Result in Eye Irritation, Contact with Skin may Cause Dermatitis, Ingestion may Cause Abdominal Pain, Vomiting and Diarrhea. High Vapour Concentration May Produce Nausea, Vomiting, Headaches, Dizziness, Unconsciousness and Asphyxia Resulting In Central Nervous System Effects.			
Effects of Chronic Exposure to Material Some Individuals may become Sensitized to Material over Time. (See Below)			
LD50 of Material Specify Species and Route Not Available	LC50 of Material Specify Species Not Available	Teratogenicity of Material Not Applicable	Mutagenicity of Material Not Applicable
Sensitization Capability of Material Skin and Respiratory	Carcinogenicity of Material Not Applicable	Reproductive Toxicity of Material Not Applicable	Synergistic Materials None Known
Exposure Limits of Material (TLV) Nepheline Syenite – TWA 10 mg/m3 (Ontario), Styrene Monomer, Inhibited – TWA 20ppm (ACGIH), Titanium Dioxide – TWA 10 mg/m3 (ACGIH)			
SECTION 7 – PREVENTATIVE MEASURES			
Personal Protective Equipment Wear Clean Long Sleeved, Body Covering Clothing, Use Impervious Gloves and Protective Clothing. Use Goggles and Full Face Shield. When Respiratory Protection is Required, Use an Approved Air Purifying Respirator. (See Below)			
Gloves (Specify) Impervious Type (Neoprene, PVC, Butyl)	Respiratory (Specify) Approved Air Purifying Respirator (Organic Vapour Cartridge)	Eye (Specify) Chemical Goggles	
Footwear (Specify) Work Boots	Clothing (Specify) Clean Long Sleeved, Body Covering (Overalls, Tyvek Suit)	Other (Specify) Full Face Shield	
Engineering Controls (Specify e.g. Ventilation Enclosed Process) Provide General Dilution of Local Exhaust in Volume and Pattern to Keep TLV of Hazardous Ingredients in Section 6 Below Acceptable Limits.			
Leak and Spill Procedure Remove All Sources of Ignition, Provide Adequate Ventilation. Avoid Prolonged Breathing of Vapours. Remove to a Container or Absorb with Clay, Diatomaceous Earth or Other Inert Absorbent.			
Waste Disposal **DO NOT INCINERATE CLOSED CONTAINERS** Incineration or Landfill in an Approved Site in Accordance with Local and Federal Regulations.			
Handling Procedure and Equipment Avoid Inhalation, Skin and Eye Contact. Practice Good Personal Hygiene. Wash Repeatedly with Soap and Water After Use and Before Work Breaks.			
Storage Requirements Keep Containers Closed and in a Cool Dry Place.			
Special Shipping Information			

SECTION 8 – FIRST AID MEASURES		
<p>EYE CONTACT – Flush Thoroughly with Water for at Least 15 Minutes. Get Immediate Medical Attention.</p> <p>SKIN CONTACT – Wash the Exposed Areas with Soap and Water Immediately. Call a Physician if Irritation Persists.</p> <p>INHALATION – Remove to Fresh Air. If Breathing is Difficult Administer Oxygen.</p> <p>INGESTION – Do Not Induce Vomiting, Administer Large Amounts of Milk or Water if Available. Transport to a Medical Facility.</p>		
Sources Used		
H & S Data from Raw Material Suppliers.		
Additional Information		
DISCLAIMER AND LIMITATION OF LIABILITY		
<p>While DENSO NORTH AMERICA INC. believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of the test conducted, the data is not to be taken as warranty or representation for which DENSO NORTH AMERICA INC. assumes legal responsibility. They are offered solely for your consideration, investigation, and verification. Final determination of the suitability of the material for the use contemplated, the manner of use, and whether the suggested use infringes any patent is the sole responsibility of the buyer.</p>		
CONFIDENTIALITY CLAUSE		
<p>It is agreed and understood that the information supplied herein is the property of DENSO NORTH AMERICA INC. It is not to be divulged in any manner to anyone whatsoever by the customer nor by anyone acting on behalf of the customer. The customer shall be responsible for any loss suffered by DENSO NORTH AMERICA INC. if the information is divulged to anyone.</p>		
SECTION 9 – PREPARATION OF THE MSDS		
Prepared by (Group, Department, etc.) Denso North America Inc.	Phone Number (416) 291-3435	Date January 1, 2014