

# MARMON/KEYSTONE LLC

THE PIPE AND TUBING PEOPLE

P.O. BOX 992, Butler, PA 16003-0992  
EMERGENCY PHONE NUMBER (724) 283-3000

ISSUE DATE:  
JANUARY 1, 2011

## MATERIAL SAFETY DATA SHEET

TRADE NAME (Common Name or Synonym)  
**Chrome Plated Carbon Steel**

CHEMICAL NAME  
**Chrome Plated 1045, 1050**

### I. INGREDIENTS

Material or Component	CAS Number	% Weight	EXPOSURE LIMITS	
			OSHA PEL (mg/m <sup>3</sup> )	ACGIH TLV (mg/m <sup>3</sup> )
Base Metal				
Iron (Fe)	1309-37-1	95-99	10 (Oxide Fume)	5 (As Iron Oxide)
Alloying Elements				
Aluminum (Al)	7429-90-5	<2	15 Dust	10 (Dust)
Carbon (C)	7440-44-0	<2	N/A	3.5 AS Carbon Black
Manganese (Mn)	7439-96-5	<2	5	5 (Dust Ceiling)
Bismuth (Bi)	7440-69-9	<1	N/A	N/A
Chromium(Cr)	7440-47-3	<1	1 (Cr. & insol. salts)	.5
Copper (Cu)	7440-50-8	<1	0.2	1 (Dust & Mist)
Molybdenum (Mo)	7439-98-7	<1	5	10 (insol. salts)
Nickel (Ni)	7440-02-0	<1	1.0	1.0
Niobium (Nb)	7440-03-1	<1	N/A	N/A
Phosphorous (P)	7723-14-0	<1	0.1 (as yellow Phos.)	N/A
Silicon (Si)	7440-21-3	<1	15 Dust	10 Total Dust
Sulfur (S)	7704-34-9	<1	13 (as SO <sub>2</sub> )	5 (as SO <sub>2</sub> )
Vanadium (V)	7440-62-2	<1	0.05 (V <sub>2</sub> O <sub>5</sub> dust & fume)	0.05 (V <sub>2</sub> O <sub>5</sub> ) dust & fume)
Metallic Coating				
Chromium (Cr)	7440-47-3	>98	1 (Cr. & insol. salts)	0.5

Note: The above listing is a summary of elements used in alloying steel. Various grades of steel will contain different combinations of these elements. Trace elements may also be present in minute amounts. No permissible exposure limits (PEL) or threshold limit values (TLV) exist for steel. Values shown are applicable to component elements.

### II. PHYSICAL DATA

MATERIAL IS (At Normal Conditions) <input type="checkbox"/> LIQUID <input checked="" type="checkbox"/> SOLID <input type="checkbox"/> GAS <input type="checkbox"/> OTHER	APPEARANCE AND ODOR Grey w/Metallic Luster, Odorless	% VOLATILE BY VOLUME N/A	VAPOR DENSITY N/A
ACIDITY/ALKALINITY pH = N/A	Melting Point Greater than 1600 °F Boiling Point N/A °F	Specific Gravity (H <sub>2</sub> O) = 1) Approx. 7 Solubility in water (% by weight) N/A	VAPOR PRESSURE (mm Hg at 20° C) N/A

### III. PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION Appropriate dust/mist/fume respirator should be used to avoid excessive inhalation of particulates. If exposure limits are reached or exceeded, use NIOSH approved equipment.	HANDS, ARMS AND BODY Protective gloves should be worn as required for welding, burning or handling operations.
EYES AND FACE Safety glasses should be worn when grinding or cutting. Face shields should be worn when welding or cutting.	OTHER CLOTHING AND EQUIPMENT As required depending on operations and safety codes.

### IV. EMERGENCY MEDICAL PROCEDURES

INHALATION:	Remove to fresh air; if condition continues, consult a physician.
EYE CONTACT:	Flush thoroughly with running water to remove particulate; obtain medical attention.
SKIN CONTACT:	Remove particles by washing thoroughly with soap and water. Seek medical attention if condition persists.
INGESTION:	If significant amounts of metal are ingested, consult physician.

## V. HEALTH/SAFETY INFORMATION

<b>Health</b>	<p>Steel products in their solid state present no inhalation, ingestion, or contact health hazard. Operations such as burning, welding, sawing, grinding, and machining, which result in elevating the temperature of the product to, or above its melting point, or result in the generation of airborne particulates may present hazards. The major exposure hazard is inhalation. Effects or overexposure to fume and dust are as follows:</p> <p><b>ACUTE:</b> Excessive inhalation of metallic fumes and dust may result in irritation of eyes, nose and throat. High concentrations of fumes and dusts of iron-oxide, manganese, copper, zinc and lead may result in metal fume fever. Typical symptoms last from 12 to 48 hours and consist of a metallic taste in the mouth, dryness and irritation of the throat, chills and fever.</p> <p><b>CHRONIC:</b> Chronic and prolonged inhalation of high concentrations of fumes or dust of the following elements may lead to the conditions listed opposite the element:                  Aluminum: May initiate fibrotic changes to lung tissue                  Bismuth: No chronic debilitating symptoms indicated                  Chromium: Lesions of the skin and mucous membranes, possibly cancer of the nose or lungs-bronchogenic carcinoma                  Copper: No chronic debilitating symptoms indicated                  Iron: Siderosis, pulmonary effects. No chronic debilitating symptoms indicated                  Manganese: Bronchitis, pneumonitis, lack of coordination                  Molybdenum: Respiratory tract irritation, possible liver and kidney damage, bone deformity                  Nickel: Lesions of the skin and mucous membranes, possibly cancer of the nose or lungs-bronchogenic carcinoma                  Phosphorous: Necrosis of the mandible                  Sulfur: (As sulfur dioxide) Edema of the lungs                  Vanadium: (As vanadium pentoxide) Emphysema, pneumonia</p> <p><b>MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:</b> Individuals with chronic respiratory disorders (i.e.: asthma, chronic bronchitis, emphysema, etc.) may be adversely affected by any fume or airborne particulate matter exposure.</p> <p><b>OCCUPATIONAL EXPOSURE LIMITS:</b> See Products Ingredients Section I. Chromium and Nickel have been identified by the International Agency for Research on Cancer (IARC) and/or the National Toxicology Program (NTP) as potential cancer causing agents.</p>			
<b>Fire and Explosion</b>	<b>FLASH POINT</b> N/A ° F	<b>AUTO IGNITION TEMPERATURE</b> N/A	<b>FLAMMABLE LIMITS IN AIR</b> Lower N / A % Upper / %	<b>EXTINGUISHING MEDIA</b> For molten metal use dry powder or sand.
	<b>FIRE AND EXPLOSION HAZARDS</b> Steel tubular products do not present fire or explosion hazards under normal conditions. Fine metal particles such as produced in grinding or sawing can burn. High concentrations of metallic fines in the air may present an explosion hazard.			<b>EXTINGUISHING MEDIA NOT TO BE USED</b> Do not use water on molten metal.
<b>Reactivity</b>	<b>STABILITY</b> <input checked="" type="checkbox"/> Stable <input type="checkbox"/> Unstable		<b>INCOMPATIBILITY (MATERIALS TO AVOID)</b> Reacts with strong acids to form hydrogen gas.	
	<b>CONDITIONS TO AVOID:</b> Steel at temperatures above the melting point may liberate fume containing oxides of iron and alloying elements. Avoid generation of airborne fume and dust.			
	<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b> Metallic dust or fumes may be produced during welding, burning, grinding and possibly machining. Refer to ANSI Z49.1.			

## VI. ENVIRONMENTAL

<p><b>SPILL OR LEAK PROCEDURES</b></p> <p>Fine turnings and small chips should be swept or vacuumed. Scrap metal can be reclaimed for re-use.</p> <p><b>WASTE DISPOSAL METHOD*</b></p> <p>Used or unused product should be disposed of in accordance with Federal, State or Local Laws and Regulations.                  *Disposer must comply with Federal, State and Local disposal or discharge laws.</p>
--

## VII. ADDITIONAL INFORMATION

<p>In welding, precautions should be taken for airborne contaminants which may originate from components of the welding rod. Arc or spark generated when welding or burning could be a source of ignition for combustion and flammable materials.</p>
<p><b>DISCLAIMER</b></p> <p>The information in this MSDS was obtained from sources which we believe are reliable, however, the information is provided without any representation or warranty, express or implied, regarding the accuracy or correctness.</p> <p>The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.</p>